



akrylmetal
BY SYNPO

PUTTY LV PTE 0530

Polyester Spatula Applied Putty with Short Curing Time

Usage	For filling of metallic surfaces, car bodies, for leveling of small unevenness on metal surface.
Substrate	Perfectly de-rusted and degreased surfaces; Old coats cleaned and degreased; Surfaces finished with anticorrosion paints Akrylmetal LV PL, LV AKZ, LV EPS or with alkyd, epoxy, water-based paints. When applied to freshly zinc-plated sheet metal, the surface should first be pre-treated with a reactive paint (such as S 2008).
Hardening component	Initiator LV BP 200
Pot life of mixed coating	min. 5 min at 20 °C
Topcoats	All types of common paints
Mixing ratio	putty : initiator 100 weight parts : 1.5 – 2.0 weight parts
Cleaning of tools	Thinners C 6000, B 6000
Application	Clean spatula
Curing time to dry-to-sand	30 minutes at 20 °C
Sanding	Wet abrasive paper no. 120 – 240 Dry abrasive paper no. 100 - 220
Caution	When handling the product follow all safety precautions indicated in the Material Safety Data Sheet and the label. Flammable liquid, Hazard Class II. Contains organic solvents. Store in a dry place at temperatures from 10 °C to 25 °C.