

Solvent-based Lacquer TUG

Solvent-based paint, transparent

DESCRIPTION

Solution of alkyd resin in organic solvents with special additives. Paint is produced in glossy or semi-gloss version.

USAGE

Top-coat is designated for inner application. It is not certified for direct food contact. Suitable for reconstruction of memorials since twenties of Twentieth Century.

MANIPULATION

Lacquer can be applied by common technique as brushing, rolling or spraying. Diluting of lacquer with thinner based on aromates is necessary at brushing or rolling; starting ratio top-coat/thinner is 4:1 by weight for glossy version, 3:1 for semi-gloss version.

PRODUCT PROPERTIES

Solids content: ca. 50 wt. %

Density: 0,97 g/cm³

Drying at 23 °C and dry film thickness 20 µm

Dust-free: within 2 hrs.

Touch-free: 24 hrs.

PACKAGING

The product is supplied in 1, 5 or 10 kg cans (or according to customer requirements).

STORAGE

Product should be stored in a covered, dry place. The temperature of storage and transport should not be below 5°C or above 25°C. Under these conditions the expected shelf life is 6 months.

SAFETY DATA

Flammable liquid. Very good ventilation and use of protective goggles and gloves is recommended. Detailed information is contained in the MSDS.

REMARKS

Information about product properties and application procedures has been obtained by laboratory measurements and application tests. This Information Sheet presents only legally non-obligatory recommendations and product application methods must be in conformity with particular conditions. For further information don't hesitate to contact us.